




[Home](#) | [Who We Are](#) | [How To Reach Us](#) | [Check Factory Stock](#) | [Product Finder](#) | [Competitors Cross Reference](#) | [Distributor Finder](#) | [Sales Rep Finder](#) | [Press Releases](#) | [Other Products: LCDs, LEDs & Transformers](#) | [Employment Opportunities](#) | [Business Opportunities](#) | [Special Promotion](#) | [More Info](#)

## AZ830 - POLARIZED DIP SINGLE SIDE STABLE RELAY

### Features:


- Meets FCC Part 68.302 and 68.304
- Bifurcated contacts (PdAg available)
- Polarized coil
- DIP package
- High sensitivity, 96 mW pickup



<b>Epoxy Sealed</b>	<b>Contact Form</b>	<b>Contact Rating</b>	<b>Coil Voltages</b>
Yes	2 Form C	2 Pole: 2 A at 30 VDC - 1 A at 120 VAC	5 thru 48 VDC
<b>Coil Power at Pickup Voltage (typical)</b>			<b>Dielectric Strength (at sea level for 1 min.)</b>
Standard Coils: 200 mW; Sensitive Coils: 100 mW Ultra-Sensitive Coils: 96 mW			Contact to Coil: 1500 Vrms Between Open Contacts: 1000 Vrms Contact Set to Contact Set: 1000 Vrms
<b>Typical Life - Electrical</b>			<b>Typical Life - Mechanical</b>
500,000 operations at 2 A / 30 VDC or 1 A / 125 VAC Resistive 2,000,000 operations at 1 A / 30 VDC or 0.5 A / 125 VAC			100,000,000 operations
<b>Terminals PC</b>	<b>Terminals Solder / Plug-In</b>	<b>Terminals Bracket Mount</b>	<b>Approvals</b>
THT	No	No	UL

<b>Minimum Load:</b>
10 mV, 10 uA

<b>Size in Inches (L x W x H):</b>
2 Form C: 0.788 x 0.390 x 0.386



### What you can do next:

- [Click here for part number ordering information](#)
- [Click here to request a quotation](#)
- [Download full product spec in Adobe Acrobat format](#)
- [Download product drawing in AutoCAD or DXF format for your symbol library](#)
- [Download our Relay Selection Guide \(Approximate size 1.7 MB in PDF-Format\)](#)
- [Get more info \(ask a question, request catalog, etc.\)](#)
- [View UL Recognized component card \("Yellow card"\)](#) [US](#) / [Canada](#)
- [Download Temperature Rise Calculator](#)

Copyright © 1999-2004 American Zettler, Inc., a [Zettler Components Company](#)

All rights reserved.

Tel: (949)831-5000 Fax: (949)831-8642

Email: [sales@zettler.com](mailto:sales@zettler.com) | Web: [www.zettler.com](http://www.zettler.com)